



9420 Santa Anita Avenue
Rancho Cucamonga, CA 91730-6117
(909) 987-0550 (800) 538-3091
Fax: (909) 987-0490
<http://www.pacertechnology.com>

PRODUCT SALES SHEET

Zap-A-Dap-A-Goo II

Zap-A-Dap-A-Goo II (PT-12) is a single component adhesive that glues, seals and repairs, dries to a flexible, rubber-like consistency and is best used for:

- Metal
- Plastics
- Ceramics
- Wood
- Glass
- Rubber
- Brick
- Concrete

PROPERTIES:

Initial color: Clear

Final color: Hazy clear to light yellow

Open Time: 1-2 minutes

Full Strength: 24-36 hours

Operating Temperature Range: -20⁰ to 150⁰F
(-29⁰ to 66⁰C)

USE INSTRUCTIONS: Use in a well-ventilated area. Protect work surfaces.

As a glue: Apply to both surfaces and let dry 1-2 minutes. Press parts together. Full cure in 24-36 hours. For rough, uneven or very porous surfaces, apply a thick layer to both surfaces and wait 30 minutes before joining parts.

As a sealer: Fill crack or hole with extra amounts and allow to dry. Add additional adhesive as needed.

For repair: To repair, apply with a spatula behind, through and above the tear or hole. Hold sides together using a strong piece of tape across the tear to hold it tightly. Remove tape after 3 hours. Remove excess with rubber eraser. Note: when thick layers are required it is better to apply a number of thin coats. Allow to cure. Full cure in 24-36 hours.

Helpful Hint: A slight hesitation in pulling the tube away from the applied Zap-A-Dap-A-Goo II product will prevent stringing.

Notes: Solvents may evaporate from bottle or tube if left open for prolonged periods. Not recommended for Teflon, Polyethylene or Polypropylene bonding. Avoid constant submergence in water and exposure to extremely high temperatures after cure.

STORAGE AND SHELF LIFE: Clean tube threads before replacing cap. Store in cool area away from sunlight or heat. Stored under these conditions, a one-year shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS

Contains Aliphatic petroleum distillate and propyl acetate. DANGER: liquid adhesive is Flammable. Harmful or fatal if swallowed. Vapor harmful. Avoid breathing vapors and contact with skin or eyes. Use and store in well-ventilated area away from heat, sparks or flame. May cause eye/skin irritation. In case of eye contact, flush with water for 15 minutes and seek medical advice. If swallowed, contact physician immediately and show the container label. Wash hands & skin with soap and water after use. **KEEP OUT OF REACH OF CHILDREN.**

For more information, refer to Material Safety Data Sheet available upon request or obtain from our ZAP Glue website @ www.zapglue.com

In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 637-0803 (outside CA only) or (909) 987-0550.

08/03-mkr

The data contained herein is furnished for descriptive purposes only and is believed to be reliable. Users of any products described in the data sheet have the responsibility to determine the suitability for their particular use thereof, and Pacer relies upon such users to adopt all necessary precautions to ensure the protection of property and persons against hazards involved in the use thereof.

Pacer Technology specifically makes no warranty, representation, or condition of any nature, kind or character, whether express or implied, including, but not limited to, warranties or merchantability or fitness for a particular purpose arising from the sales or use of products described in this data sheet, and none shall be implied by law. Pacer Technology specifically disclaims any liability for consequential or incidental damage of any kind, including lost profit.