



9420 Santa Anita Avenue
Rancho Cucamonga, CA 91730-6117
(909) 987-0550 (800) 538-3091
Fax: (909) 987-0490
<http://www.pacertechnology.com>

PRODUCT SALES SHEET

Zip Kicker

Pacer Technology Hobby Zip Kicker (PT-715, PT-29) and Zip Kicker Aerosol (PT-15, PT-50) are solvent-based accelerators to be used with Super Glues and all of the Zap line quick set adhesives. The Zip Kicker formula will force the immediate cure of all cyanoacrylates, but will not craze most plastic surfaces. Zip Kicker expands the gap filling ability of the adhesives, permits structural fillet forming and solves most tough-to-bond combinations of surface materials.

PROPERTIES: Appearance: Thin, straw-colored liquid with ketone odor.

USE INSTRUCTIONS: (NOTE – Not for use in cosmetic applications).

1. Use in a well-ventilated area with fresh air source.
2. Product can be applied to surfaces prior to application of adhesive to set adhesive surface.
3. Using Zip Kicker can influence the overall strength of adhesive bonds.

STORAGE AND SHELF LIFE

Store in cool area away from sunlight or heat. Stored under these conditions, a one-year shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS

Contains aliphatic petroleum & aromatic amine. **DANGER:** Vapor harmful. Harmful or fatal if swallowed. Product is flammable. Use & store in well-ventilated area away from heat or flame. Avoid prolonged breathing of vapor. If swallowed, do not induce vomiting. Call physician immediately and show container label. Contains a bittering agent to discourage ingestion. **KEEP OUT OF REACH OF CHILDREN.**

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm.

PT-15, PT-50 Aerosol: Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

For more information, refer to Material Safety Data Sheet available upon request or obtain from our ZAP Glue website @ www.zapglue.com.

In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 637-0803 (outside CA only) or (909) 987-0550.

Rev. 1 - 06/04-mkr

The data contained herein is furnished for descriptive purposes only and is believed to be reliable. Users of any products described in the data sheet have the responsibility to determine the suitability for their particular use thereof, and Pacer relies upon such users to adopt all necessary precautions to ensure the protection of property and persons against hazards involved in the use thereof.

Pacer Technology specifically makes no warranty, representation, or condition of any nature, kind or character, whether express or implied, including, but not limited to, warranties or merchantability or fitness for a particular purpose arising from the sales or use of products described in this data sheet, and none shall be implied by law. Pacer Technology specifically disclaims any liability for consequential or incidental damage of any kind, including lost profit.