



9420 Santa Anita Avenue
Rancho Cucamonga, CA 91730-6117
(909) 987-0550 (800) 538-3091
Fax: (909) 987-0490
<http://www.pacertechnology.com>

PRODUCT SALES SHEET

Zap Gel

Zap Gel (PT-26, PT-27) is a quick-setting, non-sagging gel formula adhesive that bonds through oily or dirty surfaces. This product is fuel-resistant & works best on:

- Wood
- Veneers
- Cork
- Rubber
- Leather
- Most Plastics
- Metals

NOTE: Not for use with Teflon, polyethylene, polypropylene, certain silicone rubber types, glass, rear view mirrors or parts that are subjected to great shock or continuous immersion in water.

PROPERTIES:

Initial color: Clear, transparent

Final color: Clear

Set time: 35-60 seconds

Full Strength: 24 hours

Operating Temperature Range: -65⁰ to 180⁰F
(-54⁰ to 82⁰C)

USE INSTRUCTIONS: NOTE: For best results, surfaces should be clean and dry.

1. Protect clothing and work surfaces (metal foil works well). Use in a well-ventilated area. Carefully follow tube-opening directions on package. Open while keeping tube pointed away from face.
2. Apply to one surface, using 1 drop per square inch of surface. Assemble parts and hold together with pressure for 15 seconds or until set.
3. Wipe top of nozzle if adhesive has accumulated before recapping tube securely after use.

STORAGE AND SHELF LIFE: Store upright in a cool area away from sunlight or heat sources. Stored under these conditions, a one-year shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS

Contains cyanoacrylate. CAUTION: Eye Irritant. Bonds skin & eyes in seconds. Use with adequate ventilation. Avoid contact with clothing as can cause burn. In case of eye contact, flush with water for 15 minutes; get medical attention for eye or internal contact. To remove from skin, soak in acetone nail polish remover & gently peel adhesive off with fingernail; water exposure will wear off residual adhesive in a few days (do not use polish remover around eye area). **KEEP OUT OF REACH OF CHILDREN.**

Statement for Europe: DANGER: Cyanoacrylate. Bonds skin & eyes in seconds. Keep out of reach of children.

For more information, refer to Material Safety Data Sheet available upon request or obtain from our ZAP Glue website @ www.zapglue.com.

In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 637-0803 (outside CA only) or (909) 987-0550.

08/03-mkr

The data contained herein is furnished for descriptive purposes only and is believed to be reliable. Users of any products described in the data sheet have the responsibility to determine the suitability for their particular use thereof, and Pacer relies upon such users to adopt all necessary precautions to ensure the protection of property and persons against hazards involved in the use thereof.

Pacer Technology specifically makes no warranty, representation, or condition of any nature, kind or character, whether express or implied, including, but not limited to, warranties or merchantability or fitness for a particular purpose arising from the sales or use of products described in this data sheet, and none shall be implied by law. Pacer Technology specifically disclaims any liability for consequential or incidental damage of any kind, including lost profit.