



9420 Santa Anita Avenue
Rancho Cucamonga, CA 91730-6117
(909) 987-0550 (800) 538-3091
Fax: (909) 987-0490
<http://www.pacertechnology.com>

PRODUCT SALES SHEET **Hobby: Z-Poxy Finishing Resin System**

Z-Poxy Finishing Resin System (PT-40) is an equal mix, thin epoxy formula used for sheeting foam wing panels and other areas requiring multiple thin coating layers. Long cure formula for easy application, sands easily for a smooth finish and is compatible with many polyester resins.

PROPERTIES

Initial color: Light yellow

Final color: Light yellow

Handling Time: 2 hours

Sanding Time: 6-8 hours

Full Strength: 24 hours

Mix Ratio: 1 part resin/1 part hardener

Operating Temperature Range: -40°F to +176°F
(-40°C to +80°C)

USE INSTRUCTIONS

1. Surfaces should be clean and dry, free from oil and grease.
2. Roughen surfaces with emery cloth or sandpaper for best results.
3. Dispense equal amounts from both bottles and mix thoroughly, approximately 1 minute.
4. Apply thin coating over surfaces. If using with fiberglass cloth, lay cloth over resin coating and allow time for resin to saturate cloth. Use soft plastic spreader to smooth wrinkles and bubbles from cloth and remove any excess resin. Remove excess epoxy immediately with denatured alcohol.
5. Allow Finishing Resin to set up for 2 hours minimum before trimming excess cloth. Allow 6-8 hours before sanding (temperature above 65F). Colder temperatures slow cure rate.
6. Full cure after 24 hours at room temperature (above 65F to 80F).

STORAGE AND SHELF LIFE

After use, wipe tips to remove residual product and reseal with plug. Store product sealed, with tips up, in a cool, dry location. Stored under these conditions, a one-year shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS

Contains Epoxy resin & Polyamide hardener. May cause sensitization and eye/skin irritation with direct contact. In case of direct eye contact, flush with water for 15 minutes and consult physician. Wash hands and skin thoroughly with soap and water after use. If swallowed, seek medical advice immediately and show container label. Keep out of reach of children.

For more information, refer to Material Safety Data Sheet available upon request or obtain from our ZAP Glue website @ www.zapglue.com.

In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 637-0803 (outside CA only) or (909) 987-0550.

06/03-mkr

The data contained herein is furnished for descriptive purposes only and is believed to be reliable. Users of any products described in the data sheet have the responsibility to determine the suitability for their particular use thereof, and Pacer relies upon such users to adopt all necessary precautions to ensure the protection of property and persons against hazards involved in the use thereof.

Pacer Technology specifically makes no warranty, representation, or condition of any nature, kind or character, whether express or implied, including, but not limited to, warranties or merchantability or fitness for a particular purpose arising from the sales or use of products described in this data sheet, and none shall be implied by law. Pacer Technology specifically disclaims any liability for consequential or incidental damage of any kind, including lost profit.